

## CLAIMS

What is claimed is:

- 1 1. A computing device comprising:  
2 a display;  
3 a memory to store a data collection, the data collection being segmented into a  
4 plurality of pages, each page being presentable on the display;  
5 a processor coupled to the display and the memory, the processor being configured to  
6 present the pages on the display by retrieving the pages from the memory and by signaling  
7 the display to present the plurality of pages; and  
8 a sensor device coupled to the processor, the sensor device sensing a deflection of a  
9 member to signal the processor a deflection value, the deflection value causing the processor  
10 to sequentially present at least portions of multiple pages on the display over an interval of  
11 time.
- 1 2. The computing device of claim 1, wherein the display is deflectable and  
2 coupled to the sensor device so as to deflect with the sensor device.
- 1 3. The computing device of claim 1, wherein the member is a component  
2 of the sensor device.
- 1 4. The computing device of claim 2, wherein the sensor device measures  
2 an analog value corresponding to a deflection of the sensor device.
- 1 5. The computing device of claim 2, wherein the sensor device is  
2 integrated with the display.

1 6. The computing device of claim 5, wherein at least a first area of the  
2 display is overlaid on the sensor device to deflect with the sensor device.

1 7. The computing device of claim 5, wherein the display is deflectable to  
2 be able to cantilever with the sensor device.

1 8. The computing device of claim 3, wherein the analog value correlates to  
2 a magnitude of the deflection.

1 9. The computing device of claim 8, wherein the magnitude of the  
2 deflection determines a frequency at which the portions of the multiple pages  
3 are presented on the display.

1 10. The computing device of claim 1, wherein the processor displays during  
2 the interval at least portions of a current page and a subsequent page, the  
3 subsequent page having a proximity to the current page in a pre-determined  
4 order of the data collection, and wherein the analog value determines the  
5 subsequent page by determining the proximity of the subsequent page to the  
6 current page.

1 11. The computing device of claim 10, wherein a length of the interval is  
2 determined by the analog value.

1 12. The computing device of claim 11, wherein the interval corresponds to  
2 when the sensor device is deflected.

1 13. The computing device of claim 3, further comprising an analog to digital  
2 converter to signal the processor a digital value corresponding to the analog  
3 value measured by the sensor device.

1 14. The computing device of claim 1, further comprising a digitizer coupled  
2 to the display.

1 15. The computing device of claim 14, wherein the sensor device is unitarily  
2 formed with the digitizer.

1 16. The computing device of claim 14, wherein the display is overlaid on  
2 the digitizer, and the sensor device is connected to the digitizer and positioned  
3 underneath the digitizer.

1 17. A computing device comprising:  
2 a deflectable display;  
3 a memory to store a data collection, the data collection being segmented into a  
4 plurality of pages;  
5 a processor coupled to the display and the memory, the processor configured to  
6 present the pages on the display by retrieving the pages from the memory and by signaling  
7 the display to individually present each of the plurality of pages; and  
8 a sensor device coupled to the display to detect a deflection of the display, the sensor  
9 device being coupled to signal the processor a deflection value corresponding to the  
10 deflection of the display;



1 23. The computing device of claim 17, wherein the processor is configured to  
2 sequentially assign the discrete elements in the first area of the display corresponding values  
3 stored for select pages in the data collection so that the discrete elements are sequentially  
4 assigned values from one of the select pages in the identified set of pages.

1 24. The computing device of claim 17, wherein the processor sequentially assigns values  
2 to each of the discrete elements in the first area of the display while the display is being  
3 deflected, the value assigned to each discrete element corresponding to one of the select  
4 pages in the identified set of pages.

1 25. The computing device of claim 17, wherein for each of the select pages, the processor  
2 signals only some of the discrete elements in the first area of the display values from that  
3 page.

1 26. The computing device of claim 25, wherein the plurality of discrete elements are  
2 arranged into rows and columns to form the display, and the processor assigns only some of  
3 the rows in the first area of the display values stored with each of the multiple pages.

1 27. A method for displaying information on a computing device assembly, the method  
2 comprising:

3 measuring a deflection of a surface of the computing device assembly;

4 accessing a data collection, the data collection being segmented into a plurality of  
5 pages;

6 in response to measuring the deflection,

7 selecting multiple pages from the plurality of pages using the measured deflection; then

8 displaying at least portions of the multiple pages sequentially over an interval of time.

1 28. The method of claim 27, wherein measuring the deflection of the surface includes  
2 measuring a deflection of a display for the computing device.

1 29. The method of claim 27, wherein measuring the deflection of the surface includes  
2 measuring a deflection of a sensor device integrated with the surface.

1 30. The method of claim 27, further comprising implementing a frequency at which each  
2 of the multiple pages are sequentially displayed, wherein the frequency is based on the  
3 measured deflection.

1 31. The method of claim 27, wherein the plurality of pages are arranged into an order,  
2 and wherein the method includes displaying at least portions of the multiple pages  
3 sequentially according to the order of the plurality of pages.

1 32. The method of claim 30, wherein the frequency is proportional to the measured  
2 deflection.

1 33. The method of claim 32, wherein the predetermined order indicates a position of each  
2 page relative to the other pages, and wherein displaying at least portions of the multiple  
3 pages includes displaying portions of selected pages that are separated by other pages in the  
4 predetermined order.

1 34. The method of claim 33, wherein displaying at least portions of selected pages  
2 includes displaying the selected pages sequentially according to a direction of the selected  
3 pages in the predetermined order.

1 35. The method of claim 33, including displaying portions of the multiple pages  
2 sequentially according to a decreasing direction of the numbers for the multiple pages

1 36. The method of claim 27, wherein measuring a deflection includes determining an  
2 analog value corresponding to a magnitude of the deflection.

1 37. A handheld computing assembly comprising:  
2 a handheld computer comprising a display, a processor coupled to the display, and a  
3 memory, the memory storing a data collection segmented into a plurality of pages, the  
4 processor being configured to access the data collection stored in the memory and to signal  
5 the display to individually present each page of the data collection; and  
6 an analog input device coupled to the handheld computer, the analog input device  
7 including a deflectable sensor device that signals a deflection value to the processor when  
8 deflected;  
9 wherein the deflection value signals the processor to sequentially display at least  
10 multiple pages from the plurality of pages on at least a portion of the display.

1 38. A peripheral device for a handheld computer, the handheld computer comprising a  
2 display, a processor coupled to the display, and a memory, the memory storing a data  
3 collection arranged into a plurality of pages, the processor being configured to access the  
4 memory and to signal the display to individually present each of the pages, the peripheral  
5 device comprising:  
6 a communication port to extend communications between the peripheral device and  
7 the handheld computer; and

8 an analog input device coupled to the processor of the handheld computer via the  
 9 communication port, the analog input device including a deflectable sensor device that  
 10 signals a deflection value to the processor when deflected, the deflection value causing the  
 11 processor to sequentially display at least portions of multiple pages from the plurality of  
 12 pages on at least a portion of the display of the handheld computer.

1 39. A method for displaying information on a computing device assembly, the method  
 2 comprising:

3 measuring an analog input from a user;  
 4 accessing a memory to identify a plurality of pages from a data collection;  
 5 in response to receiving the analog input;  
 6 selecting multiple pages from the plurality of pages based on a value of the analog  
 7 input; then  
 8 sequentially displaying at least portions of the multiple pages.

1 40. The method of claim 39 wherein displaying at least portions of the multiple includes  
 2 selecting the multiple pages based on the value of the analog input.

1 41. The method of claim 39 where displaying at least portions of the multiple includes  
 2 displaying the pages sequentially at a frequency that is based on the value of the analog  
 3 input.

1 42. The method of claim 39 wherein the multiple pages are arranged into a predetermined  
 2 order, and the method includes displaying at least portions of the multiple pages in a  
 3 sequenced based on the predetermined order.



1 43 A computing device comprising:  
2 a display;  
3 a processor configured to signal the display to sequentially present a plurality of  
4 pages; and  
5 an input mechanism that deflects to signal the processor to repaginate the content  
6 presented on the display.

1 44. The computing device of claim 43, wherein the processor is configured to present  
2 individual pages of the content on the display, and wherein the input mechanism deflects to  
3 signal the processor to present another page of the paginated content on the display.

1 45. The computing device of claim 44, wherein the input mechanism deflects to signal  
2 the processor to present a series of pages of the paginated content on the display.

1 46. The computing device of claim 43, wherein the input mechanism deflects to detect an  
2 analog value.